

88 SERIES



SPECIFICATIONS	88M1	88M1-A1
TYPE OF VEHICLE (4x4)	Compact, Mid-Size Truck or SUV (ex. Ford Explorer, Jeep Grand Cherokee)	
RECOMMENDED MAX GVW	8,800 lbs GVW	
RECOMMENDED MAX SPEED	40 mph	
FRAME CONSTRUCTION	Steel	
STEERING ASSIST UPGRADE (ADDS 25 LBS)	N/A	Yes
ASSEMBLY WEIGHT	361 lbs	380 lbs
INTERNAL SUSPENSION	Concentric Pivot	Concentric Pivot, Rocker Arm
TRACK TREAD WIDTH	16"	
TRACK TREAD STYLE	All-Terrain, Self-Cleaning	
TRACK MATERIAL	Rubber with Internal Composite Rods/Cord	
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°	
AXLE HEIGHT	20.25"	
GROUND CONTACT LENGTH	(Hard Surface) 33" / (Soft Surface) 52"	
GROUND CONTACT SURFACE AREA	656 in ² min / 944 in ² max	
SPROCKET DIAMETER	18.5"	
WHEELS TYPE	8" x 2"	
ROAD WHEEL COUNT	8, 2 rows	
WHEEL MATERIAL	UMHW / Rubber	
PAINT COLOR	Silver Metallic (Standard, other colors available)	

* ALL SPECS ARE PER CORNER

MODELS IN SERIES: 88M1, 88M1-A1, 88M1-A1-SA



JEEP FC-150 ON 88M1-A1



HUMMER H3 ON 88M1-A1



TOYOTA LAND CRUISER ON 88M1-A1

MATTRACKS
RUBBER TRACK CONVERSIONS

ALL SPECIFICATIONS ARE APPROXIMATE AND WE RESERVE THE RIGHT TO MAKE CHANGES OR MODIFICATIONS WITHOUT NOTIFICATION

202 Cleveland Ave E · PO Box 214 · Karlstad, MN 56732 · 877.436.7800 · mattracks.com