

EZ SERIES



SPECIFICATIONS	EZ ATV	EZ UTV	EZ MAXIM (REAR ONLY)	EZ HD
TYPE OF VEHICLE	ATV	UTV	UTV	UTV, Small SUV
RECOMMENDED MAX GVW	2,500 lbs	3,500 lbs	3,500 lbs	5,500 lbs
FRAME CONSTRUCTION	Steel			
SPROCKET DRIVE UPGRADE	Yes			N/A
ASSEMBLY WEIGHT	135 lbs	146 lbs	194 lbs	170 lbs
SUSPENSION	N/A			
TRACK TREAD WIDTH	13"			
TRACK TREAD STYLE	All-Terrain, Self-Cleaning			
RUBBER TRACK CONSTRUCTION	Rods, Std Ply, Std Cord	Rods, HD Ply, Std Cord		
RECOMMENDED OPERATING TEMP	(Ambient) -40°F to +130°			
GROUND CONTACT LENGTH	(Hard Surface) 14" (Soft Surface) 45"	(Hard Surface) Fr: 14" / Rr: 21" (Soft Surface) Fr: 45" / Rr: 52"	(Hard Surface) Fr: 14" / Rr: 21" (Soft Surface) Fr: 45" / Rr: 73"	(Hard Surface) 21" (Soft Surface) 49"
GROUND CONTACT SURFACE AREA	(Hard Surface) 728 in ² (Soft Surface) 2,360 in ²	(Hard Surface) 910 in ² (Soft Surface) 2,524 in ²	(Hard Surface) 910 in ² (Soft Surface) 3,086 in ²	(Hard Surface) 910 in ² (Soft Surface) 2,379 in ²
SPROCKET DIAMETER	13" to 15.5"			17"
ROAD WHEEL COUNT	10, 2 rows	10 Front, 12 Rear, 2 rows	10 Front, 12 Rear, 2 rows	12, 2 rows
WHEEL MATERIAL	UMHW / Rubber			
PAINT COLOR	Yellow (Standard, other colors available)			

* ALL SPECS ARE PER CORNER

MODELS IN SERIES: EZ ATV, EZ UTV, EZ MAXIM, EZ HD



ARCTIC CAT 500 ON EZ ATV



POLARIS RANGER CREW 900 ON EZ UTV



CHEVY TRACKER ON EZ HD