

TRAIL-R-MATE



SPECIFICATIONS	ATV	65	Standard	Pneumatic	HD
TYPE OF VEHICLE	ATV Utility Trailers	Utility Trailers			
RECOMMENDED MAX GVW	1,200 lbs	4,000 lbs	8,000 lbs		12,000 lbs
RECOMMENDED MAX SPEED	40 mph				
FRAME CONSTRUCTION	Steel				
INTERNAL SUSPENSION	Rigid, Oscillating	N/A	Concentric Pivot	Concentric Pivot with Air Ride Pneumatic	Concentric Pivot with Oscillating Rocker Arm Suspension
TRACK TREAD WIDTH	11"	15"	16"		18"
TRACH TREAD STYLE	All-Terrain, Self-Cleaning				
TRACK MATERIAL	Rubber with Internal Composite Rods and Cord				
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°				
GROUND CONTACT LENGTH	(Hard Surface) 36" (Soft Surface) 42"	(Hard Surface) 31" (Soft Surface) 49"	(Hard Surface) 36" (Soft Surface) 51"	(Hard Surface) 41" (Soft Surface) 59"	(Hard Surface) 38" (Soft Surface) 58"
GROUND CONTACT SURFACE AREA	924 in ²	1,329 in ²	1,632 in ²	1,888 in ²	1,740 in ²
ROAD WHEEL COUNT	10, 2 rows	6, 2 rows	6, 2 rows	6, 2 rows	8, 2 rows
WHEEL MATERIAL	UMHW / Rubber				
PAINT COLOR	Yellow (Standard, other colors available)			Red (Standard, other colors available)	Yellow (Standard, other colors available)
	* ALL SPECS ARE PER CORNER - Note: Track images not to scale across models				