

# TRACK-TOR-ASSIST

FOUR-WHEEL DRIVE WITH FRONT WHEEL ASSIST



SPECIFICATIONS	3500	5000	6000	7000	8000
TYPE OF VEHICLE	Four-wheel drive with front wheel assist				
RECOMMENDED MAX GVW	7,000 lbs	10,500 lbs	14,250 lbs	19,000 lbs	23,000 lbs
RECOMMENDED MAX SPEED	20 mph				
FRAME CONSTRUCTION	Front: Aluminum Rear: Steel	Steel			
INTERNAL SUSPENSION	Front: Concentric Pivot with Adjustable Spring Rocker Arm Rear: Concentric Pivot with Rocker Arm	Concentric Pivot with Rocker Arm Air Ride Pneumatic on 5000 & 7000 Rear Track Only			
TRACK TREAD WIDTH	Front: 11" / Rear: 16"	16"	Front: 16" / Rear: 18"	18"	
TRACK TREAD STYLE	All-Terrain, Self-Cleaning				
TRACK MATERIAL	Rubber with Internal Composite Rods and Cord				
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°				
GROUND CONTACT LENGTH	(Hard Surface) Front: 24" / Rear: 30" (Soft Surface) Front: 36" / Rear: 52"	(Hard Surface) Front: 30" / Rear: 41" (Soft Surface) Front: 52" / Rear: 62"	(Hard Surface) Front: 33" / Rear: 41" (Soft Surface) Front: 51" / Rear: 56"	(Hard Surface) Front: 41" / Rear: 43" (Soft Surface) Front: 56" / Rear: 62"	(Hard Surface) Front: 43" / Rear: 56" (Soft Surface) Front: 62" / Rear: 70"
GROUND CONTACT SURFACE AREA	Front: 528 in <sup>2</sup> min / 792 in <sup>2</sup> max Rear: 960 in <sup>2</sup> min / 1,664 in <sup>2</sup> max	Front: 960 in <sup>2</sup> min / 1,664 in <sup>2</sup> max Rear: 1,312 in <sup>2</sup> min / 1,984 in <sup>2</sup> max	Front: 1,056 in <sup>2</sup> min / 1,632 in <sup>2</sup> max Rear: 1,476 in <sup>2</sup> min / 2,016 in <sup>2</sup> max	Front: 1,476 in <sup>2</sup> min / 2,016 in <sup>2</sup> max Rear: 1,548 in <sup>2</sup> min / 2,232 in <sup>2</sup> max	Front: 1,548 in <sup>2</sup> min / 2,232 in <sup>2</sup> max Rear: 2,016 in <sup>2</sup> min / 2,520 in <sup>2</sup> max
SPROCKET DIAMETER	Front: 14" / Rear: Varies by vehicle	Varies by vehicle			
WHEELS TYPE	Front: (4) 10" x 1.25", (4) 6" x 1.25" Rear: 8" x 2.5" HD Extra Seals	8" x 2.5" HD Extra Seals			
ROAD WHEEL COUNT	Front: 8, 2 rows Rear: 8, 2 rows	Front: 8, 2 rows Rear: 10, 2 rows	Front: 8, 2 rows Rear: 12, 3 rows	Front: 12, 3 rows Rear: 15, 3 rows	Front: 15, 3 rows Rear: 18, 3 rows
WHEEL MATERIAL	UMHW / Rubber				
PAINT COLOR	Yellow (Standard, other colors available)				
	* ALL SPECS ARE PER CORNER - Note: Track images not to scale across models				