

TRACK-TOR-ASSIST

FOUR-WHEEL DRIVE



SPECIFICATIONS	3535	5050	6060	7070	8080
TYPE OF VEHICLE	Four-wheel drive				
RECOMMENDED MAX GVW	11,500 lbs	14,000 lbs	17,000 lbs	21,000 lbs	25,000 lbs
RECOMMENDED MAX SPEED	20 mph				
FRAME CONSTRUCTION	Steel				
INTERNAL SUSPENSION	Concentric Pivot with Rocker Arm Air Ride Pneumatic on 5050 & 7070 Only				
TRACK TREAD WIDTH	16"		18"		
TRACK TREAD STYLE	All-Terrain, Self-Cleaning				
TRACK MATERIAL	Rubber with Internal Composite Rods and Cord				
RECOMMENDED OPERATING TEMP	(Ambient) -40° to +130°				
GROUND CONTACT LENGTH	(Hard Surface) 30 in (Soft Surface) 52 in	(Hard Surface) 41 in (Soft Surface) 62 in	(Hard Surface) 41 in (Soft Surface) 56 in	(Hard Surface) 43 in (Soft Surface) 62 in	(Hard Surface) 56 in (Soft Surface) 70 in
GROUND CONTACT SURFACE AREA	960 in ² min / 1,664 in ² max	1,312 in ² min / 1,984 in ² max	1,476 in ² min / 2,016 in ² max	1,548 in ² min / 2,232 in ² max	2,016 in ² min / 2,520 in ² max
SPROCKET DIAMETER	Varies by vehicle				
WHEELS TYPE	8" x 2.5" HD Extra Seals				
ROAD WHEEL COUNT	8, 2 rows	10, 2 rows	12, 3 rows	15, 3 rows	18, 3 rows
WHEEL MATERIAL	UMHW / Rubber				
PAINT COLOR	Yellow (Standard, other colors available)				
	* ALL SPECS ARE PER CORNER - Note: Track images not to scale across models				